

Claims

[c1][currently amended]

Having thus described the invention, what is claimed as new and useful and is desired to be secured by U.S. Letter Patent is:

A nasal cannula assembly designed for contact with the nasalabidial area of a patient's nose and comprising:

a hollow tubular member having an opening at each end, said tubular member having a central portion of sufficient length to span the width of an average patient's nostrils and end portions extending from each end of said central portion, said central portion having a pair of spaced, hollow extensions integral with and projecting therefrom said hollow extensions terminating in gas directing orifices and which hollow portion of said extensions communicate with said hollow main body portion,

said central portion lying in a first plane with longitudinal axes symmetrical

essentially parallel to and displaced from said first plane,

said end portions of said central portion lying in essentially the first plane with longitudinal axis of said end portion essentially collinear with longitudinal axis of corresponding symmetrical half of said central portion.

[c2][previously presented]

A nasal cannula assembly as recited in claim 1, wherein said hollow extensions terminate in said gas directing orifices where thickness of material forming rim of said orifices is less than .006 inches.

[c3][previously presented]

A nasal cannula assembly as recited in claim 1, wherein longitudinal axis of each said gas directing orifice angled acutely in said second plane toward second said gas directing orifice.

[c4] [currently ammended]

A nasal cannula assembly designed for contact with the nasalabidial area of a patient's nose and comprising at least one support tube having a 10% tensile modulus less than 200 psi.

~~a hollow tubular member having a central portion of sufficient length to span the width of an average patient's nostrils and end portions with openings of a diameter to receive support tubing,~~

~~flexible support tube fitted to open end of each said end portion.~~

[c5][previously presented]

A nasal cannula assembly as recited in claim 4 wherein said support tubes have a hardness between 40 and 75 Shore A.

[c6][previously presented]

A nasal cannula assembly as recited in claim 4 wherein said support tubes have a compression set less than 45% at 23 degrees C per ASTM D-395.

[c7][previously presented]

A nasal cannula assembly as recited in claim 4 wherein said support tubes have a brittle temperature less than -40 degrees C per ASTM D-746.

[c8][canceled]

[c9][previously presented]

A nasal cannula assembly as recited in claim 4 wherein said support tubes are manufactured from a polyvinyl chloride compound comprising at least a portion of polyvinyl chloride resin having an average molecular weight of at least about 100,000.

[c10][currently amended]

A nasal cannula assembly designed for contact with the nasalabidial area of a patient's nose and comprising at least one main supply tube having a 10% tensile modulus less than 200 psi.

~~with and projecting therefrom said extensions terminating in gas directing orifices and which hollow portion of said extensions communicate with said hollow main body portion,~~

~~a pair of spaced hollow extensions communicating with the interior of said tubular member and extending away from the member for directing fluid into the nostrils of the patient and/or receiving gas or pressure variations from the nostrils of the patient;~~

~~open end of each said end portion accepting support tubes;~~

~~each said support tube having an opposite open end affixed to a common coupling with hollow interior communicating with both said support tubes;~~

~~said coupling having a third opening communicating with said hollow interior and accepting open end of a flexible main supply tube.~~

[c11] [previously presented]

A nasal cannula assembly as recited in claim 10 wherein main supply tube has a hardness between 40 and 75 Shore A.

[c12][previously presented]

A nasal cannula assembly as recited in claim 10 wherein main supply tube has a compression set less than 45% at 23 degrees C per ASTM D-395.

[c13][previously presented]

~~polyvinyl chloride resin having an average molecular weight of at least about 100,000.~~

[c16]-(c19)[canceled]